All For Better Networking

4G301

WiFi Anywhere, Anytime

Compatible with 4G/3G mobile broadband modems
Internal 5200mAh battery

Wireless N300 3G/4G Router

networks. By plugging an activated FDD-LTE/TD-LTE/HSPA+/HSPA/HSDPA/EVDO modem, and it turns 4G/3G signal into a high speed WiFi Hotspot with data rate of up to 300Mbps. Whether you're on the road, at airport, or camping, you can always instantly set up a WiFi hotspot and share by your companions. It provides an Ethernet port, so that you can connect it to an existing wired network using an Ethernet cable and enjoy Internet activities like surfing, chatting, and streaming video wirelessly. In addition, for increased mobility, the device is built with an internal battery with a capacity of 5200mAH. It gives you freedom to roam anywhere anytime. Ideal for people who are on the go.

Easy 3G/4G Sharing

By inserting an activated TD-LTE/FDD-LTE USB modem, this 802.11n compliant router gives you freedom to roam and still remain connected to the Internet. It is also backward compatible with 3G networks including WCDMA and CDMA 2000.

Internal 5200mAh Battery

Designed with internal 5200mAh battery, the device is able to work for up to 15 hours for regular Internal activities. Meanwhile it can provide power source for your smartphones and tablets. It is good to fully charge a smartphone for 3-4 times.

Make Wired Wireless

Plug an Ethernet cable into the device and connect it to your exisisting wired network, it turns the wired connection into a WiFi hotspot, so that your smartphone, laptop, or tablet can access to Internet and share wirelessly and simultaneously.

Specifications

Hardware Specification	Protocol Standard	IEEE 802.11b.IEEE 802.11g.IEEE 802.11n.IEEE 802.3u
	Port	1*RJ-45 1*USB 2.0 1*Micro USB
	Antenna	2* Internal Antennas
	Button	Switch Button Reset Button
	Power Source	Input：(VAC）100-240V；50Hz Output：(VDC) 5V，1.2A
	Capacity	2600mAh
	Product Size（L*W*H）	89.9mm*41.6mm*38.9mm
	LED Indicator	1* Capacity LED Indicator
Wireless Parameter	Wireless Network Rate	300Mbps
	Frequency	2.4GHz
	Basic Function	Modify network mode,SSID,Broadcast,Channel,Channel Bandwidth
	Wireless Security	Support WPA-PSK,WPA2-PSK,WPA&WPA2-PSK mixed and a series of encryption and security
Software Features	WAN Accessing Method	3G/4G,PPPOE,DHCP,Static
	Operating Mode	Family,Hotel,3G/4G,WISP
	DHCP Configuration	DHCP Server Client Lisst Static Address Assignment
	Virtual Server	Port Transmit DMZ Host
	Security Configuration	Client Filter Mac Address Filter URL Filter Remote WEB Management
	VPN Penetration	Support
	DDNS	88ip.cn/3322.org/no-ip.com/DynDNS.com
Additional Information	Temperature	Operating temperature：-10℃ to 40℃； Storage temperature：-40℃to 70℃
	Humidity	Operating Humidity：10% to 90%RH Non-condensing Storage Humidity：5% to 90%RH Non-condensing
	Default Settings	SSID:Tenda+the last six numbers of MAC address Wireless Password：None Default Access Method：DHCP
	Certification	FCC/CE/RoHS/WEEE
	Associated Products	4G301,4G302,3G189E,3G-W6
	Packing Accessories	4G300*1 Quick Installation Guide *1 Network Cable *1 USB Cable *1 Warranty Card *1

SHENZHEN TENDA TECHNOLOGY CO.,LTD.
No. 34-1 Shilong Road Shiyan Town, Baoan District Shenzhen 518108,China
Phone: (86 755) 2765 7180 Fax:(86 755) 2765 7178
Email: sales@tenda.com.cn support@tenda.com.cn
http://www.tendacn.com

©2013 SHENZHEN TENDA TECHNOLOGY CO.,Ltd, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.